



ROBUST DESIGN

Built for high-volume applications in demanding production and back-office environments - with a lifespan of 5 years or 24 million pages

HIGH SPEED RELIABILITY

600dpi, 32 pages per minute, up to 400,000 pages per month duty cycle - with minimal maintenance requirements

EASE-OF-USE

Quick warm-up time, high toner capacity, quiet operation, small footprint and user-friendly supplies and components servicing

MAXIMUM EFFICIENCY

Straight-through path for continuous-form paper or label stock, reversible drive and leading edge self-alignment reduces wastage of media

WIDE RANGE OF OPTIONS

Including Power-Assisted or Full-Power Stacker, Cutter, Magnetic Ink Character Recognition (MICR)

LEADERSHIP BY DESIGN

Printronix provides market-leading continuous form printing solutions designed with the capacity, reliability, and versatility needed for production environments - delivered globally through our network of sales, support and logistics locations.

Extending this leadership further is the Laserline L7032. The L7032 delivers a winning combination of print quality, speed, ease-of-use, footprint, media handling and affordability. Rated at 32 pages per minute and up to 400,000 pages per month, this printer is ideal for use in distribution, supply chain and manufacturing applications.

MAXIMUM PRINTING - MINIMUM MAINTENANCE

The L7032 is designed specifically for high volume, mission-critical applications, with high reliability and ease-of-use, easy serviceability to minimize cost and repair time, and minimal user maintenance requirements.

Each consumable and service item delivers extended life to minimize the number of user interventions. When items do need refreshing, they can be easily replaced in minutes by the user/operator without tools or special training. Long life coupled with ease-of-use creates a printing solution that reliably delivers high volume throughput.

CONTINUOUS FORMS ADVANTAGE

Continuous form laser printers combine high-resolution printing and speed with the ability to handle challenging forms not possible with cut sheet feeders. They also allow large volume print runs with a broad range of paper sizes, high duty cycles with power stacking and/or cutting of output. The straight paper path and positive engagement pin feed drive system also ensures print jobs run jam and misalignment free. In addition, continuous forms printing offers the advantage of keeping forms together and in sequence.

Robust continuous form laser printers from Printronix are the ideal choice for production printing applications.



PRINTRONIX®

GLOBAL PRINTING...ENABLED.

SPEED

Pages-Letter Landscape	32 ppm
Pages-Letter Portrait	25 ppm
Lines Speed	1650 lpm @ 6 LPI
Plot Speed	275 ipm

FIRST PAGE SPEED

Initial From Power Up	<200 seconds
From Standby	<45 seconds
Ready State	<20 seconds

TECHNOLOGY

Imaging	Laser
Fusing	Heat and pressure
Drum Type	OPC
Paper Path	Straight through

RESOLUTION

Standard	600 x 600 dpi
Software Selectable	300 x 300 dpi

WORKLOAD

Monthly Workload	400,000 pages (8.5" x 11" landscape)
Maximum Total Pages	24,000,000 pages (8.5" x 11" landscape)
Design Life	5 years

REPLACEMENT INTERVALS*

Toner	32,000 pages @ 4% coverage
Waste Toner Container	64,000 pages
Felt Wiper	64,000 pages
OPC Cartridge	400,000 pages
Developer Unit	800,000 pages
Fuser Unit	800,000 pages

*All items are end user replaceable - life time based on 75 grams/m² fanfold paper

MEDIA TYPES

Type	Pin fed continuous plain paper, label stock, card stock and tag stock
Weight	60 to 160 grams/m ² 16 lbs to 42 lbs bond 33 - 116 lbs index 36 - 129 tag & label
Thickness	0.014" (0.35mm) max
Width	7.0" (178mm) min to 15.5" (394mm) max
Length	3" (76mm) min to 33" (825mm) max

PRINTABLE AREA

Print Width	13.6" (345mm)
Print Height	Up to full form length - no margin required

INTERFACES

Parallel	IEEE-1284 (standard)
Ethernet	10/100 Base T (standard)

SYSTEM CONNECTIVITY

Emulation	PCL5e
Drivers	Windows 2000/NT/XP

PRINTER FEATURES

Optional	Cabinet stand Power assist stacker (PAS) Full power stacker (FPS) Cutter MICR toner
----------	---

POWER

Consumption	1.3 kW max 700 W - during printing 70 W - stand by mode
Line voltage	100 - 240VAC +/- 10 %
Line frequency	50/60 Hz

ENVIRONMENTAL

Operating Temperature	10° - 32° C (50° - 90° F)
Operating Humidity	20 - 80% Relative Humidity
Maximum Altitude	7,500 ft (2,286m)
Acoustic Noise	<55 dBA

DIMENSIONS

	Printer	W/ Cabinet and PAS	W/ Cabinet and PAS	W/ FPS
Height	16.5" (42cm)	48" (122cm)	48" (122cm)	46" (117cm)
Width	24" (61cm)	40" (102cm)	63" (160cm)	39" (99cm)
Depth	24" (61cm)	25" (63.5cm)	25" (63.5cm)	25" (63.5cm)
Shipping Weight	134 lbs (61kg)	50 lbs (23kg)	65 lbs (30kg)	133 lbs (60.5kg)

Dimensions include the printer and option
Weights are individual items

GENUINE PRINTRONIX SUPPLIES

Choosing the right supplies is critical for life of the printer, print quality, image durability and total cost of operation. Protect your investment with Genuine Printronix Supplies.



Southern Europe - PRINTRONIX France Sarl
8, rue Parmentier, F-92800 Puteaux, France
Tel: +33 (0) 1 46 25 19 00

Central Europe - PRINTRONIX Deutschland GmbH
Goethering 56, D-63067 Offenbach, Germany
Tel: +49 (0) 69 82 97 06 0

Northern Europe - PRINTRONIX UK Ltd
Forth House, 4 Brants Bridge, Bracknell,
Berkshire RG12 9BG, UK
Tel: +44 (0) 1344 869666

Eastern Europe - PRINTRONIX Österreich GmbH
Schönbrunner Schlossstraße 5, A-1120 Wien, Austria
Tel: +43 (0) 1 810 39 60

Iberia - PRINTRONIX Iberica SL
C/ Arte 21 - 4C, 28033 Madrid, Spain
Tel: +34 91 76 80 850

Russia and C.I.S., PRINTRONIX Inc,
Moscow Representative Office
Balakirevsky per., 19, office 106,
105082 Moscow, Russian Federation
Tel: +7 (495) 737 9387

Middle East and Africa - PRINTRONIX, Inc. MEA
Gulf Business Centre, Crown Plaza Commercial Tower,
Sheikh Zayed Road, P.O.Box : 62425, Dubai, UAE
Tel: +971 4 3328276

Customer Support Centre EMEA,
PRINTRONIX Netherlands BV
Nieuweweg 283, P.O. Box 163,
NL-6600 AD Wijchen, Netherlands
Tel: +31 (0) 24 64 89 489

For further information about our products and services, please visit our website at:
www.primtronix.com

For sales enquiries, please email:
emeasales@primtronix.com

For technical support, please email:
emeasupport@primtronix.com